

Safety regulations

ADMIRAL Couplers can only be installed or used by competent and/or qualified personnel.

Before using a Coupler you should inspect them visually for any damage. If the coupler is damaged you should be taking it out of service and return it to your local ADMIRAL dealer for inspection.

ADMIRAL Coupler RIHAHCA48 is designed to specifically attach to round tubes of \varnothing 48-51mm and is forbidden to be used in falsework structures.

During installation of the Coupler you must take care not to overtighten the wing nut or wing handle. This to prevent damage to the tube and/or the Clamp/Coupler. If you use only one wing nut or wing handle, it is preferred to only hand tighten it. When you use an additional nut, below the wing nut or wing handle, follow this torque setting: Max. 22-25 N-m.

ADMIRAL Coupler RIHAHCA48 comes with an indicated WLL of 200kg. This WLL may not be exceeded or any other max. load given as instructed during installation. Couplers that are being used in combination with accessories, should never exceed the max. load of the used accessory.


WARNING

Always make sure you double lock the ADMIRAL Couplers, with e.g. two nuts.



Half coupler 48-51mm lifting eye

ADMIRAL CODE:



RIHAHCA48

EAN



A product of ADMIRAL

Josink Kolkweg 10, 7545 PR Enschede
The Netherlands, +31 534 301 201



USER MANUAL



Half coupler 48-51mm lifting eye



www.admiralstaging.com

Half coupler



Ø 32 - 35mm
WLL 75kg



Ø 48 - 50mm
WLL 100kg



Ø 48 - 51mm
WLL 200kg



Ø 48 - 51mm
WLL 200kg



Ø 48 - 51mm
WLL 500kg



Ø 48 - 51mm
WLL 750kg

Half coupler with lifting eye



Ø 48 - 51mm
WLL 200kg

Swiffel coupler

Ø 48 - 50mm
WLL 100kg



Ø 48 - 51mm
WLL 200kg



Ø 48 - 51mm
WLL 500kg

ADMIRAL CLAMPS AND COUPLERS

Admiral supplies a vast array of clamps and couplers, from aluminum half couplers to swivel couplers with a WLL up to 750kg.

Quick coupler



Ø 48 - 51mm
WLL 250kg

Selflock coupler



Easy
Ø 48 - 51mm
WLL 250kg



Shorty
Ø 48 - 51mm
WLL 100kg

C-clamp



Ø 48 - 50mm
23cm/40cm/60cm

G-clamp



Ø 48 - 50mm
23cm/40cm/60cm

G-clamp straight



Ø 48 - 50mm
WLL 50kg

Qwiqr



With the Qwiqr you connect your hooks onto a luminaire with only one click.

Slide the hook into the housing and click!

Safety cable



Mount the safety cable in a small loop to absorb the weight when falling. Accident avoided.

60 cm / 100 cm

complies with BGV-C1